



KS600 - platen

Basis boxen

Plaat lengte	Plaat hoogte	Plaat dikte	Vrije lengte tussen stempels	Vrije ruimte onder stempels	Max. grond- druk	Gewicht per box
(mm)	(mm)	(mm)	(mm)	(mm)	(kN/m ²)	(kg)
4000	2600	100	3600	1550	35,60	2560
4000	2400	100	3600	1550	35,60	2400
4000	1650	100	3600	800	35,60	1695
3500	2600	100	3100	1550	40,70	2320
3500	2400	100	3100	1550	40,70	2180
3500	1650	100	3100	800	40,70	1495
3000	2600	100	2600	1550	47,50	2075
3000	2400	100	2600	1550	47,50	1950
2500	2600	100	2100	1550	52,30	1820
2500	2400	100	2100	1550	52,30	1724
2000	2600	100	1600	1550	65,10	1578
2000	2400	100	1600	1550	65,10	1496

Opzet boxen

Plaat lengte	Plaat hoogte	Plaat dikte	Vrije lengte tussen stempels	Vrije ruimte onder stempels	Max. grond- druk	Gewicht per box
(mm)	(mm)	(mm)	(mm)	(mm)	(kN/m ²)	(kg)
4000	1400	100	3600	1550	35,60	1492
3500	1400	100	3100	1550	40,70	1348
3000	1400	100	2600	1550	47,50	1204

